



TECHNICAL DATA:

Not easily accessible device, according to standard EN 1176-1:2017

Device dimensions: 3,92 x 5,05m Device height: 2,20m Minimum space: 7,77 x 8,80m Falling area: 55,42m² Critical fall height: 2,20m


Foundations depth: -0,50 / -0,80m


The device according to EN 1176-1:2017 Playground equipment and surfacing – Part 1: General safety requirements and test methods.

Safety surfaces:

- sand, gravel, bark, synthetic surface
- minimal thickness for loose particulate materials 300+100mm synthetic surface according to critical fall height

Top view with falling area





Construction pole 4 pcs Construction pole: steel profile, galvanized, powder coated in gray Climbing wall 4 pcs Climbing wall: rotomolded polypropylene Caps: plastic Foundations: concrete min. C12/15 standard



SATERNUS DISTRIBUTION Sp. z o.o. sp.k. ul. Nowa 32 41-500 Chorzów, Poland

Certificate beholder: Producer: Distributor: GRUPA SATERNUS Sp. z o.o. S. K. A. reserves all rights to protect copyright under the Act of February 4, 1994 on Copyright and Related Rights (Journal of Laws No. 28, pc 83), and in particular Art. 78 and 79 of this Law.

GRUPA SATERNUS Sp. z o.o. S. K. A. Saternus Production Sp. z o.o. sp. k. Saternus Distribution Sp. z o.o. sp. k.